

KSR-204

Stand Alone DVR



1 MAIN FUNCTION

- **REAL TIME MORNING** : Simultaneous live images
- **EASY PICTURE RETRIEVAL** : Instant picture retrieval by date/time and camera number
- **COMPACT PICTURE STORAGE** : Images are compressed down to an average of file size between 2-3kb per picture using Engine-X Algorithm (Engine-X is a unique Kodicom development)
- **EVENT CONTROLLED RECORDER** : Reduces the amount of data and automatically records specific events.
- **PICTURE TRANSMISSION OVER NETWORK** :
High quality picture transmission over PSTN, ISDN & LAN network
- **EMERGENCY ALARM** : Automatic transmission to a monitoring center
- **MULTI SCREEN MORNING** : 1, 4 Split Screen available
- **REMOTE CONTROL** : Remote Control of PTZ cameras & other electronic devices

2 FEATURES

- 4Ch cameras real-time display and recording
- High image quality
- High speed network transmission
- Include various functions(motion detection, schedule, backup, etc.)
- Easy to use GUI(Graphical User Interface)

3 APPLICATION


Bank, Apartment, Casino, Airport, Military, Jewelry store, Hospital, Car Pard, Department store, and etc.

KSR-204


SURVEILLANCE SCREEN




>> OUTWARD APPEARANCE



UPPER



REAR





FRONT



SIDE

>> CONFIGURATION



- Split screen : 1~4 cameras
- Live Display
- Digital Zoom
- User Defined Motion Detection with Audible Alarm
- Easy Operation with User Friendly GUI and On-screen Menu

SEARCH SCREEN



- Search by Date, Time and Camera .
- Various Search Functions : Play back, forward & backward, skip, slow motion, pause, frame by frame, zoom in/out and brightness control etc.
- Intelli-Search Function

PAN/TILT SCREEN



- Control of up to 4PTZ cameras (RS-422 and RX Receiver-option)
- Functions : Pan, Tilt, Zoom, Focus and Presets

>> SPECIFICATION

		KSR-204
Image Display & Recording Speed	NTSC	Display : 4CH 120 Frame/Sec (MAX) Recording : 4CH MAX 30 Frame/Sec, AVG 2~3Kb
	PAL	Display : 4CH 100 Frame/Sec, 2~3kb Recording : 4CH MAX 25 Frame/Sec, AVG 2~3Kb
Image Compression Method		Engine-X
Screen Division		1, 4 Division
Camera Input		4CH
External Monitor		CVBS : 1, S-Video : 1
External Sensor Input		4CH
Control Output		4CH
Remote Transmission		LAN/PSTN (Optional)
Surveillance Method		Motion Detection / Sensor
PAN/TILT		RS-422
AUDIO		1CH
USB Support		YES